


NASA Facts

National Aeronautics and
Space Administration

Dryden Flight Research Center

P.O. Box 273
Edwards, California 93523
Phone 805-258-3449
FAX 805-258-3566



FS-1992-05-024-DFRC



EC 77-6981

F-8 Digital Fly-By-Wire

The Digital Fly-By-Wire (DFBW) concept utilizes an electronic flight control system coupled with a digital computer to replace conventional mechanical flight controls.

The first test of a DFBW system in an aircraft, was in 1972 on a modified F-8 Crusader at the Dryden Flight Research Facility, Edwards, California. It was the forerunner of the fly-by-wire flight control systems now used on the space shuttles and on today's military and civil aircraft to make them safer, more maneuverable, and more efficient.

Background

In the first few decades of flight, pilots controlled aircraft through direct force – moving control sticks and rudder pedals linked to cables and pushrods, that pivoted control surfaces on the wings and tails.

As engine power and speeds increased, more force was needed and hydraulically-boosted controls emerged. Soon, all high performance and large aircraft had hydraulic-mechanical flight control systems. These conventional flight control systems restricted designers in the configuration and design of aircraft because of the need for flight stability.

As the electronic era grew in the 1960s, so did the idea of aircraft with electronic flight control systems. Wires replacing cables and pushrods would give designers greater flexibility in configuration and in the size and placement of components such as tail surfaces and wings. A fly-by-wire system would be smaller, more reliable, and in military aircraft, the systems would be much less vulnerable to battle damage. A fly-by-wire aircraft would also be much more responsive to pilot control inputs. The result would be more efficient, safer aircraft with improved performance and design.

The Aircraft

By the late 1960s, engineers at Dryden began discussing how to modify an aircraft and create a digital fly-by-wire testbed.

Support for the concept at NASA headquarters came from Neil Armstrong, former research pilot at Dryden. He served in the Office of Advanced Research and Technology following his historic Apollo 11 lunar landing and knew electronic control systems from his days training in and operating the lunar module. Armstrong supported the proposed Dryden project and backed the transfer of an F-8C Crusader from the Navy to NASA to become the Digital Fly-By-Wire (DFBW) research aircraft. It was given the tail number “NASA 802.”

The entire mechanical flight control system in the F-8, including all cables, pushrods, and bell cranks, was replaced by wires – from the control stick in the cockpit, to the control surfaces on the wings and tail surfaces. The heart of the system was an off-the-shelf backup Apollo digital flight control computer and inertial sensing unit which transmitted pilot inputs to the actuators on the control surfaces.

On May 25, 1972, the highly modified F-8 became the first aircraft to fly completely dependent upon an electronic flight control system. The pilot was Gary Krier.

The first phase of the DFBW program validated the fly-by-wire concept and quickly showed that a refined system – especially in large aircraft – would greatly enhance flying qualities by sensing motion changes and applying pilot inputs instantaneously.

The Phase 1 system had a backup fly-by-wire system in the event of a failure in the Apollo computer unit, but it was never necessary to use the system in flight.

In a joint program carried out with the Langley Research Center in the second phase of research, the original Apollo system was replaced with a triple redundant digital system. It would provide backup computer capabilities if a failure occurred.

The DFBW program lasted 13 years. The final flight – the 210th of the program – was made April 2, 1985, with Dryden research pilot Ed Schneider at the controls.

Research Benefits

The DFBW F-8 validated the principal concepts of the all-electric flight control systems now used on nearly all modern high performance aircraft and on military and civilian transports. A DFBW flight control system is also used on the space shuttles.

NASA 802 was the testbed for the sidestick controller used in the F-16 fighter, the first U.S. high performance aircraft with a DFBW system.

Among other electronic milestones first flown on the DFBW F-8 were an angle-of-attack limiter and maneuver-driven flaps, features commonly used on today's new generation of aircraft.

In addition to pioneering the space shuttle's fly-by-wire flight control system, NASA 802 was the testbed that explored Pilot Induced Oscillations (PIO) and validated methods to suppress them. PIOs occur when a pilot overcontrols an aircraft and a sustained oscillation results. On the last of five free flights of the prototype space shuttle Enterprise during approach and landing tests in 1977, a PIO developed as the vehicle settled onto the runway. The problem was duplicated with the DFBW F-8 and a series of PIO suppression filters were developed and tested on the aircraft for the shuttle program office.

The aircraft was used to develop a concept called Analytic Redundancy Management, in which dynamic and kinematic relations between various dissimilar sensors and measurements are used to detect and isolate sensor failures.

In another series of successful tests, a software back-up system (Resident Backup System) was demonstrated as a means to survive common software faults which could cause all three channels to fail. This system has been subsequently used on many experimental and production aircraft systems.

The Dryden project also worked with the British Royal Aircraft Establishment using the DFBW F-8 to produce ground-based software to use when researchers are investigating flight controls in high-risk flight environments. During contingencies, pilots can disengage the ground control software and switch to backup on-board controls.

DFBW research carried out with NASA 802 at Dryden is now considered one of the most significant and successful aeronautical programs in NASA history.

Specifications

The F-8 aircraft was originally built by LTV Aerospace, Dallas, Texas, for the U.S. Navy which made it available to Dryden as a test vehicle.

- NASA 802: NAVY BUREAU #145546
- Powerplant was a Pratt and Whitney J57 turbojet
- Wingspan is 35 feet 2 inches (350 square feet)
- Overall length is 54 feet 6 inches, and height is 15 feet 9 inches
- Flown as the DFBW testbed by NASA from 1972 to 1985

Fleet F-8s were the first carrier based plane with speeds in excess of 1,000 mph. LTV won the Collier Trophy for its design and development. Total production was 1,261.

–NASA–

Modified: May 1992